



#110
FOIL SCRIM KRAFT
(FSK) TAPE
UL LISTED
 TAPE DIVISION

PRODUCT:
 Compac #110 Foil Scrim Kraft Tape (FSK) with Acrylic Adhesive.

PRINCIPAL USES:
 Compac #110 Foil Scrim Kraft (FSK) tape with Acrylic Adhesive is UL listed and is designed to provide a high quality long lasting closure material. #110 is engineered to seam and seal fiber glass duct board and duct wrap, enhancing appearance and maintaining vapor barrier integrity. Another primary use is for patching of pre-engineered metal buildings.

FEATURES AND BENEFITS:
 Compac #110 FSK Tape features an aggressive, **all-temperature rated** acrylic adhesive system that adheres tightly when smoothed down on work surfaces. Service temperatures of **-25°F (-32°C) to 150°F (66°C)** and application temperatures of **10°F (-12°C) to 150°F (66°C)** are now available through Compac technology.

Compac #110 FSK Tape carries a UL 10/0 rating on flame spread and smoke generated, far exceeding the industry standard of 25/50. Compac is known for its quality and industry leadership and remains the *only* manufacturer in the world of both vapor barrier facings and pressure sensitive insulation tapes.

TECHNICAL DATA:

<u>CATEGORY</u>	<u>DATA</u>	<u>TEST METHOD</u>
Substrate	Foil/Scrim/Kraft Laminate	
Adhesive	Acrylic (clear)	
Tape thickness without liner	8 mils (0.20 mm)	
Color	Silver Metallic	
Adhesion to Steel	90 oz/inch (98N/100mm)	PSTC - 1 ASTM D3330
Tensile Strength	30 lbs/inch (525N/100mm)	PSTC-31 ASTM D3759
Elongation	1%	PSTC-31 ASTM D3759
Permeance	0.02 Perms (0.013)	ASTM E-96
UL Recognition	UL File #R6131	UL 723 ASTM E-84
Flame Spread	10	UL 723 ASTM E-84
Smoke Generated	0	UL 723 ASTM E-84

SURFACE PREPARATION: The surface to which the tape is applied should be dry, clean, and free of grease and oil.

STORAGE TEMPERATURE: Tape should be stored in cool, dry area at temperatures of **60°F (16°C) to 80°F (-27°C)**.

CAUTION: All physical properties listed above have been obtained from random laboratory testing and should not be used for the purpose of writing specifications. **THIS PRODUCT SHOULD BE TESTED TO DETERMINE THE SUITABILITY FOR ITS INTENDED USE.**

THERE ARE NO WARRANTIES, EXPRESSED, IMPLIED OR STATUTORY, INCLUDING IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, WITH RESPECT TO THE PRODUCTS DISCUSSED HEREIN

In the event of Compac's liability, whether based on contract, tort, negligence, strict liability or otherwise, Purchaser's sole and exclusive remedy will be limited to, at Compac's option, the replacement by Compac of any nonconforming goods for which claim is made by Purchaser in accordance with these terms and conditions or to the allowance of a credit for the portion of the purchase price paid by the Purchaser attributable to the nonconforming goods. Compac shall not be liable for incidental or consequential or any other losses, damages or expenses, directly or indirectly arising from the sale, remanufacture, handling or use of the goods or from any other cause relating thereto. Any action brought relating to the goods must be commenced within one year from the date such cause of action arose.

DS-110 Rev #: 3
 Rev Date: 09/02/03