

## technical data sheet

# BOSTIK SPRAY ADHESIVE

### PRODUCT

All purpose aerosol adhesive for art and craft applications.

### DESCRIPTION

Bostik spray adhesive has a fast aggressive tack that makes it ideal for light assembly jobs and maintenance applications. Bostik Spray adhesive contains no fluorocarbons. Provides a light bond to paper cardboard, photographs, prints, artworks, wood, plastic, styrene, leather, felt, cork and fabric.

### RECOMMENDED USES

Ideal for light assembly jobs such as mounting prints or illustrations to a wide range of surfaces.

### FEATURES & BENEFITS

- Easy to use aerosol can
- Colourless fast drying adhesive
- Can be used as a permanent bond
- Can be used as a temporary bond

### PROPERTIES

Form	Aerosol spray
Appearance	White liquid with aliphatic solvent odour
Viscosity	Approximately 5000cps
Boiling point	69° C (Hexane)
Specific Gravity	Approximately 1.00 g/cm <sup>3</sup>
Vapour Pressure	Propane: 6413@21°C. mmHg
Volatile Component	Approx. 90%wgt
Fash Point	Propane = -104°C
Auto Ignition	Temp 225°C
Rel. Vapour Density	Hexane = 2.97 (air=1)
Working Time	Instant permanent stick. Allow to dry on one surface for 5 minutes for a repositional stick

### PACKAGING

Bostik Spray Adhesive is available in 350g aerosol can and is packed in a cut-case carton.

### APPLICATION INSTRUCTIONS

#### Preparation

Ensure surfaces to be bonded are clean, dry and free from grease, oil dust and other foreign materials.

#### Application

- Shake can well before use
- Hold 20-25cm away from article and spray evenly

- For a permanent bond, spray both surfaces and press together while still tacky
- For a temporary bond, spray one surface only, allow to dry and press surfaces together.
- For a porous material such as cork, felt, fabric, spray only one surface and press together while still tacky
- For bonding to polystyrene foam, apply several thin coats, not a single heavy layer.
- After use, turn can upside down, depress spray nozzle and spray until clear propellant comes out. Spray nozzles may be soaked in mineral turpentine to keep clean.
- Clean up over-spray on material, carefully remove with mineral turpentine.

### HEALTH AND SAFETY

- Avoid contact with skin and eyes and breathing in vapour.
- Intentional misuse by deliberately concentrating and inhaling contents can be harmful or fatal.
- High flammable so do not smoke

#### First Aid

If inhaled remove victim to fresh air and for all but most minor symptoms arrange for patient to be seen by a doctor. For eyes, immediately irrigate with copious quantity of water for at least 15 minutes. (eyelids to be held open) For skin, wash with plenty of soap and water.

### PRECAUTIONS

- Recommended for light assembly jobs.
- Use in a well ventilated area.
- Do not use near flame or spark producing equipment

### STORAGE

Store in cool dry, well-ventilated area. Store in original containers in an approved flammable liquid storage area. Keep containers securely sealed. Do not store or transport with oxidizing agents (Clas 5). Do not incinerate or puncture this can, even when empty.

Dangerous Goods Class 9 must be transported in accordance with State regulations.

### FIRE

Product flammable (refer MSDS)

### BOSTIK SPRAY ADHESIVE

ITEM NO.	STOCK SIZE	Unit per carton
262390	350g aerosol can	6

*The representations and recommendations regarding the products are based on tests which we believe to be reliable. However, no guarantee of their accuracy can be made because of the great range of field conditions and variations encountered in raw materials, manufacturing equipment and methods. Thus, the products are sold with a limited warranty only, and on the condition that purchasers will make their own tests to determine the suitability of the product for their particular purposes. Under no circumstances will Bostik Findley Australia Pty Ltd be liable to anyone except for replacement of the products or refund of the purchase price.*

**ALL SALES ARE EXPRESSLY LIMITED TO THE TERMS AND CONDITIONS OF SALE OF BOSTIK FINDLEY AUSTRALIA PTY LTD**

### FOR FURTHER INFORMATION



**BOSTIK FINDLEY  
AUSTRALIA PTY LTD**  
Phone: +61-3-9279 9333  
Fax: +61-3-9279 9240

**BOSTIK FINDLEY  
NZ LIMITED**  
Phone: +64-4-567 5119  
Fax: +64-4-567-5412

**BOSTIK FINDLEY  
SINGAPORE PTE LTD**  
Phone: +65-863 4088  
Fax: +65-863 4077

**BOSTIK FINDLEY  
(MALAYSIA) SDN BHD**  
Phone: +606 764 3246  
Fax: +606 764 3248

**SYDNEY**  
Phone: 02 8825 3488  
Fax: 02 8825 3411

**ADELAIDE**  
Phone: 08 8244 0511  
Fax: 08 8244 0522

**PERTH**  
Phone: 08 9331 7666  
Fax: 08 9331 7677

**BRISBANE**  
Phone: 07 3265 2377  
Fax: 07 3265 5421

**(ABN 79 003 893 838)**

Product: Bostik Spray Adhesive  
Issue Date: September 2001  
Issue No: 1  
Division: Craft & Stationery  
Total Pages: 1