

White Lightning[®]
Painter's Preferred[™]
Acrylic Latex Caulk

Physical Properties:

Type:	Acrylic Latex Caulk
Color:	Bright White
Shelf Life:	12 months
Flash Point:	N/A Water Based
Flammability:	N/A Water Based
Cure Time:	7-14 days
Tack Free Time:	5 - 7 minutes
Application Temperature:	50°F to 120°F
Service Temperature:	-30°F to 180°F
VOC Level:	.38 lb/gal
Mildew Resistance:	Good
Water Resistance:	Good
Odor:	Low/None
Shrinkage:	Low/Moderate
Vehicle:	Water
Solids by Weight:	82%
Weight/Gallon:	13.54lbs/gal

Performance Data:

Joint Movement Capability:	Low
Joint Size:	1/8" X 1/8" to _" to _"
Freeze-Thaw Stability:	Stable through 5 cycles
Durability:	25 Years
Clean Up:	Warm water
Flexibility:	Good

Surface Preparation: Clean surface free from oils, loose mortar, release agents, old caulking, old paint, or other contaminants.

Painting: Allow a minimum of two hours dry time before painting with latex or oil based paint. Allow extra dry time during periods of high humidity and/or cool temperatures

Cautions: Contains Crystalline Silica. Use only with adequate ventilation. Avoid contact with eyes and skin. Wash hands after using. Do not transfer contents to other containers for storage.

Packaging:

Color	Order #	UPC for Each	Size
White	WL30100	0-23275-30100-9	10.0 fl oz.

For more information please call or write:
White Lightning Products
101 Prospect Ave. NW
Cleveland, OH 44115
1-800-241-5295

